

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of the claims in the application.

In the Claims

1-48. (Cancelled)

49. (Currently amended) An embolectomy device for use in a blood vessel having a diameter, comprising:

a catheter having a proximal end, a distal end and a lumen extending therebetween, the lumen having a longitudinal axis extending from the proximal end to the distal end;

a vacuum source fluidly attached to the proximal end of the catheter to provide a source of vacuum to the catheter lumen;

a wire having a proximal end and a distal end and a center line extending therebetween that follows the path of the wire, the wire further having a proximal region, an intermediate region and a distal region, and the wire being at least partially disposed in the lumen,

~~wherein the intermediate region has a generally uniform width along its length,~~

wherein the distal region of the wire includes a distal tip ~~having a generally uniform profile along the center line~~ and a region proximate the distal tip having a maximum width perpendicular to the longitudinal axis of the lumen that is greater than the width of the intermediate region of the wire and wherein the distal tip has a width that is less than that of the region proximate the distal tip,

wherein the distal region includes a distal taper that is more gradual than a proximal taper.

50. (Previously presented) The embolectomy device of claim 49 wherein the distal region has a maximum width that is less than half the diameter of the blood vessel.

51. (Currently amended) The embolectomy device of claim 50 wherein the proximate region of the distal region has a curved profile with respect to [[to]] the longitudinal axis.

52. (Previously presented) The embolectomy device of claim 51 wherein the maximum width of the proximate region is at least twice the width of the distal tip.

53. (Previously presented) The embolectomy device of claim 52 wherein the cross-sectional shape of the wire along the center line is a simple closed shape.

54. (Cancelled)

55. (Previously presented) The embolectomy device of claim 49 wherein the wire is configured to move rapidly along the longitudinal axis of the lumen proximally and distally.

56. (Previously presented) The embolectomy device of claim 53 wherein the proximate region has a first section having a first end that has a maximum thickness of material perpendicular to the longitudinal axis and a second end that abuts the distal tip, the proximate region further having a second section having a first end that abuts the first end of the first section and a second end that has a width equal to that of the intermediate region of the wire,
wherein the first section is longer than the second section.

57. (Previously presented) The embolectomy device of claim 56 wherein the first section transitions gradually from the first end of the first section to the second end of the first section.

58. (Previously presented) The embolectomy device of claim 56 wherein the first section is at least twice as long as the second section.

59-63. (Cancelled)

64. (Previously presented) The embolectomy device of claim 49 wherein the distal tip and the intermediate regions have approximately the same widths.

65. (Currently amended) The embolectomy device of claim ~~[[65]]~~ 64 wherein the distal tip width is equal to that of the intermediate region.